




| | | |
|--|---|------------------|
| Bit Size Range | 4-3/4 - 5-7/8 in | 121 - 149 mm |
| Bit Box Connection | 2-7/8 REGULAR | |
| Dynamic Bearing Load On/Off Bottom | 31850 lbf | 14200 daN |
| Static Bearing Load On/Off Bottom | 104100 lbf | 46300 daN |
| Max. Overpull (For Re-run) | 154100 lbf | 68500 daN |
| Absolute Overpull | 256800 lbf | 114200 daN |
| Adjustable Makeup Torque | 3500 ft-lbs | 4700 Nm |
| Stab/Thread Protector Makeup Torque | 3500 ft-lbs | 4700 Nm |
| A = Bit to Stabilizer (Centre) | 10.7 in | 0.27 m |
| B = Bit to Bend | Adjustable 50.3 in Fixed 41.6 in | 1.28 m 1.06 m |
| C = Overall (With Dump Sub) | 231.05 in | 5.87 m |
| Weight | 508 lb | 230 kg |

| | | |
|--------------------------------------|-----------------------|-----------|
| Lobe Configuration | 7-8 Lobe 2.3 Stage HR | |
| Displacement (No Load) | 0.768 rev/gal | 0.2 rev/l |
| Max. Differential (Full Load) | 520 psi | 3585 kPa |
| Max. Torque | 1670 ft-lbs | 2264 Nm |
| Max. Power | 35 HP | 26 kW |

| Flow Rate | | Speed |
|-----------|------|-----------|
| GPM | LPM | RPM |
| 80 | 5303 | 50 - 61 |
| 120 | 454 | 80 - 96 |
| 160 | 606 | 110 - 130 |



Possible damage may occur when motor is run higher than 70% of Maximum Differential Pressure.

ADJUSTABLE BUILD RATE

| Hole Size | SLICK | | | | STABILIZED | | | |
|-------------------|----------------------------|-----------|---------------|---------------|----------------------------|-----------|---------------|---------------|
| | 4-3/4 (121mm) | 5 (127mm) | 5-1/4 (133mm) | 5-7/8 (149mm) | 4-3/4 (121mm) | 5 (127mm) | 5-1/4 (133mm) | 5-7/8 (149mm) |
| BEND ANGLE | Degrees per 100 Feet (30m) | | | | Degrees per 100 Feet (30m) | | | |
| 0.39 | 0.7 | - | - | - | 2.6 | 3.0 | 3.4 | - |
| 0.78 | 4.9 | 3.6 | 2.2 | - | 6.0 | 6.4 | 6.8 | 7.8 |
| 1.15 | 9.0 | 7.6 | 6.3 | 2.9 | 9.3 | 9.7 | 10.1 | 11.1 |
| 1.50 | 12.8 | 11.5 | 10.1 | 6.7 | 12.8 | 12.8 | 13.2 | 14.1 |
| 1.83 | 16.4 | 15.1 | 13.7 | 10.3 | 16.4 | 15.7 | 16.1 | 17.0 |
| 2.12 | 19.6 | 18.3 | 16.9 | 13.5 | 19.6 | 18.3 | 18.6 | 19.6 |
| 2.38 | 22.5 | 21.1 | 19.7 | 16.3 | 22.5 | 21.1 | 20.9 | 21.9 |
| 2.60 | 24.9 | 23.5 | 22.2 | 18.8 | 24.9 | 23.5 | 22.8 | 23.8 |
| 2.77 | 26.7 | 25.4 | 24.0 | 20.6 | 26.7 | 25.4 | 24.3 | 25.3 |
| 2.90 | 28.2 | 26.8 | 25.4 | 22.0 | 28.2 | 26.8 | 25.5 | 26.5 |
| 2.97 | 28.9 | 27.6 | 26.2 | 22.8 | 28.9 | 27.6 | 26.2 | 27.1 |
| 3.00 | 29.3 | 27.9 | 26.5 | 23.1 | 29.3 | 27.9 | 26.5 | 27.3 |

Note: Stabilizers are 1/8" undergauge

FBH BUILD RATE

| Hole Size | SLICK | | | | STABILIZED | | | |
|-------------------|----------------------------|-----------|---------------|---------------|----------------------------|-----------|---------------|---------------|
| | 4-3/4 (121mm) | 5 (127mm) | 5-1/4 (133mm) | 5-7/8 (149mm) | 4-3/4 (121mm) | 5 (127mm) | 5-1/4 (133mm) | 5-7/8 (149mm) |
| BEND ANGLE | Degrees per 100 Feet (30m) | | | | Degrees per 100 Feet (30m) | | | |
| 1.25 | 9.3 | 7.7 | 6.1 | 2.1 | 10.8 | 11.2 | 11.6 | 12.5 |
| 1.50 | 12.1 | 10.5 | 8.9 | 4.9 | 13.1 | 13.5 | 13.9 | 14.8 |
| 1.75 | 14.8 | 13.2 | 11.6 | 7.6 | 15.4 | 15.8 | 16.2 | 17.2 |
| 2.00 | 17.6 | 16.0 | 14.3 | 10.3 | 17.7 | 18.1 | 18.5 | 19.5 |
| 2.25 | 20.3 | 18.7 | 17.1 | 13.1 | 20.3 | 20.4 | 20.8 | 21.8 |
| 2.50 | 23.0 | 21.4 | 19.8 | 15.8 | 23.0 | 22.8 | 23.1 | 24.1 |

This information is for reference only. Build rates are theoretical calculations using three-point geometry and new motor builds. Actual rate predictions will depend on formation characteristics, bit profiles, and WOB.

For custom motor configurations and build rates, please contact your DYNOMAX office.

FISHING DIMENSIONS

USC - IMPERIAL (Lengths, Diameters = in)
SI - METRIC (Lengths = m, Diameters = mm)



| EXTERNALS | | USC | SI |
|------------------------------|----|-------|-------|
| END CAP | A | 5.8 | 0.15 |
| BEARING HOUSING | B | 12.0 | 0.30 |
| PISTON HOUSING | C | 18.7 | 0.47 |
| STABILIZER SHOULDER | D | 26.2 | 0.67 |
| KICK/FIXED HOUSING | E | 36.0 | 0.91 |
| BIT TO BEND (ADJUSTABLE) | F1 | 50.3 | 1.28 |
| ADAPTOR HOUSING (ADJUSTABLE) | G1 | 55.0 | 1.40 |
| BIT TO BEND (FIXED) | F2 | 41.6 | 1.06 |
| ADAPTOR HOUSING (FIXED) | G2 | 55.0 | 1.40 |
| STATOR START | H | 66.8 | 1.70 |
| STATOR END | I | 207.8 | 5.28 |
| OVERALL LENGTH | J | 231.1 | 5.87 |
| BIT BOX Ø | K | 3.60 | 91.4 |
| END CAP/BEARING HOUSING Ø | L | 3.75 | 95.3 |
| THREAD PROTECTOR Ø | M | 4.25 | 108.0 |
| PISTON HOUSING Ø | N | 3.75 | 95.3 |
| KICK/FIXED HOUSING Ø | O | 3.75 | 95.3 |
| PAD (ADJUSTABLE) Ø | P1 | 4.00 | 101.6 |
| PAD (FIXED) Ø | P2 | 4.00 | 101.6 |
| ADJUSTABLE MANDREL PIN Ø | Q | 2.10 | 53.3 |
| ADAPTOR HOUSING Ø | R | 3.75 | 95.3 |
| ADAPTOR PIN Ø | S | 2.56 | 65.0 |
| STATOR TUBE OUTER Ø | T | 3.75 | 95.3 |
| STATOR TUBE INNER Ø | U | 3.00 | 76.2 |
| ROTOR CATCH SUB BLADE Ø | V | 4.00 | 101.6 |
| ROTOR CATCH SUB Ø | W | 3.75 | 95.3 |



| INTERNALS | | USC | SI |
|----------------------------|---|-------|------|
| BIT BOX | A | 5.5 | 0.14 |
| THRUST SHOULDER | B | 13.8 | 0.35 |
| WASHPIPE START | C | 15.9 | 0.40 |
| HEX END | D | 22.2 | 0.56 |
| BEARING ASSEMBLY ADAPTOR | E | 34.9 | 0.89 |
| BAA CAP | F | 43.4 | 1.10 |
| ROTOR ADAPTOR CAP | G | 61.8 | 1.57 |
| ROTOR START | H | 67.4 | 1.71 |
| ROTOR END | I | 196.4 | 4.99 |
| CATCH STEM | J | 205.9 | 5.23 |
| BIT BOX Ø | K | 3.63 | 92.2 |
| MANDREL Ø | L | 2.75 | 69.9 |
| THRUST Ø | M | 2.00 | 50.8 |
| WASHPIPE LARGE Ø | N | 2.63 | 66.8 |
| WASHPIPE SMALL Ø | O | 2.13 | 54.1 |
| BEARING ASSEMBLY ADAPTOR Ø | P | 2.70 | 68.6 |
| DRIVESHAFT Ø | Q | 1.40 | 35.6 |
| ROTOR ADAPTOR Ø | R | 2.70 | 68.6 |
| ROTOR MAJOR DIA. Ø | S | 2.25 | 57.2 |
| ROTOR CATCH STEM Ø | T | 1.80 | 45.7 |

This information is for reference only. Assemblies are displayed in an "Adjustable Configuration"

Rotor Catch and Rotor Catch Float Sub Lengths may vary based on configuration, and use of Dump Subs or combination Rotor Catch and Float Housings.

If any additional information is required, please contact your local DYNOMAX office.