


| | | |
|--|---|------------------|
| Bit Size Range | 5-5/8 - 6-3/4 in | 143 - 171 mm |
| Bit Box Connection | 3-1/2 REGULAR | |
| Dynamic Bearing Load On/Off Bottom | 71500 lbf | 31800 daN |
| Static Bearing Load On/Off Bottom | 229350 lbf | 102000 daN |
| Max. Overpull (For Re-run) | 328000 lbf | 145900 daN |
| Absolute Overpull | 546000 lbf | 242900 daN |
| Adjustable Makeup Torque | 12000 ft-lbs | 16300 Nm |
| Stab/Thread Protector Makeup Torque | 8000 ft-lbs | 10800 Nm |
| A = Bit to Stabilizer (Centre) | 15.7 in | 0.4 m |
| B = Bit to Bend | Adjustable 55.8 in Fixed 45.6 in | 1.42 m 1.16 m |
| C = Overall (With Dump Sub) | 337.43 in | 8.57 m |
| Weight | 1318 lb | 598 kg |

| | | |
|--------------------------------------|-----------------------|------------|
| Lobe Configuration | 7-8 Lobe 4.5 Stage HR | |
| Displacement (No Load) | 0.463 rev/gal | 0.12 rev/l |
| Max. Differential (Full Load) | 1520 psi | 10480 kPa |
| Max. Torque | 5250 ft-lbs | 7118 Nm |
| Max. Power | 122 HP | 91 kW |

| Flow Rate | | Speed |
|-----------|------|-----------|
| GPM | LPM | RPM |
| 150 | 5568 | 52 - 69 |
| 225 | 852 | 87 - 105 |
| 300 | 1136 | 122 - 140 |



Possible damage may occur when motor is run higher than 70% of Maximum Differential Pressure.

ADJUSTABLE BUILD RATE

| Hole Size | SLICK | | | | STABILIZED | | | |
|-------------------|----------------------------|-----------|---------------|---------------|----------------------------|-----------|---------------|---------------|
| | 5-7/8 (149mm) | 6 (152mm) | 6-1/8 (156mm) | 6-1/4 (159mm) | 5-7/8 (149mm) | 6 (152mm) | 6-1/8 (156mm) | 6-1/4 (159mm) |
| BEND ANGLE | Degrees per 100 Feet (30m) | | | | Degrees per 100 Feet (30m) | | | |
| 0.39 | 2.6 | 2.1 | 1.7 | 1.3 | 2.6 | 2.1 | 2.0 | 2.1 |
| 0.78 | 5.5 | 5.1 | 4.7 | 4.2 | 5.5 | 5.1 | 4.7 | 4.6 |
| 1.15 | 8.3 | 7.9 | 7.4 | 7.0 | 8.3 | 7.9 | 7.4 | 7.0 |
| 1.50 | 10.9 | 10.5 | 10.1 | 9.7 | 10.9 | 10.5 | 10.1 | 9.7 |
| 1.83 | 13.4 | 13.0 | 12.6 | 12.1 | 13.4 | 13.0 | 12.6 | 12.1 |
| 2.12 | 15.6 | 15.2 | 14.8 | 14.3 | 15.6 | 15.2 | 14.8 | 14.3 |
| 2.38 | 17.6 | 17.1 | 16.7 | 16.3 | 17.6 | 17.1 | 16.7 | 16.3 |
| 2.60 | 19.2 | 18.8 | 18.4 | 17.9 | 19.2 | 18.8 | 18.4 | 17.9 |
| 2.77 | 20.5 | 20.1 | 19.6 | 19.2 | 20.5 | 20.1 | 19.6 | 19.2 |
| 2.90 | 21.5 | 21.0 | 20.6 | 20.2 | 21.5 | 21.0 | 20.6 | 20.2 |
| 2.97 | 22.0 | 21.6 | 21.2 | 20.7 | 22.0 | 21.6 | 21.2 | 20.7 |
| 3.00 | 22.2 | 21.8 | 21.4 | 21.0 | 22.2 | 21.8 | 21.4 | 21.0 |

Note: Stabilizers are 1/8" undergauge

FBH BUILD RATE


| Hole Size | SLICK | | | | STABILIZED | | | |
|-------------------|----------------------------|-----------|---------------|---------------|----------------------------|-----------|---------------|---------------|
| | 5-7/8 (149mm) | 6 (152mm) | 6-1/8 (156mm) | 6-1/4 (159mm) | 5-7/8 (149mm) | 6 (152mm) | 6-1/8 (156mm) | 6-1/4 (159mm) |
| BEND ANGLE | Degrees per 100 Feet (30m) | | | | Degrees per 100 Feet (30m) | | | |
| 1.25 | 8.9 | 8.4 | 7.9 | 7.4 | 8.9 | 8.4 | 7.9 | 8.0 |
| 1.50 | 10.8 | 10.3 | 9.8 | 9.3 | 10.8 | 10.3 | 9.8 | 9.7 |
| 1.75 | 12.7 | 12.2 | 11.7 | 11.2 | 12.7 | 12.2 | 11.7 | 11.4 |
| 2.00 | 14.5 | 14.0 | 13.5 | 13.0 | 14.5 | 14.0 | 13.5 | 13.1 |
| 2.25 | 16.4 | 15.9 | 15.4 | 14.9 | 16.4 | 15.9 | 15.4 | 14.9 |
| 2.50 | 18.3 | 17.8 | 17.3 | 16.8 | 18.3 | 17.8 | 17.3 | 16.8 |

This information is for reference only. Build rates are theoretical calculations using three-point geometry and new motor builds. Actual rate predictions will depend on formation characteristics, bit profiles, and WOB.


For custom motor configurations and build rates, please contact your DYNOMAX office.

FISHING DIMENSIONS

USC - IMPERIAL (Lengths, Diameters = in)
SI - METRIC (Lengths = m, Diameters = mm)



| EXTERNALS | | USC | SI |
|------------------------------|----|-------|-------|
| END CAP | A | 8.5 | 0.22 |
| BEARING HOUSING | B | -- | -- |
| PISTON HOUSING | C | 11.5 | 0.29 |
| STABILIZER SHOULDER | D | 26.2 | 0.67 |
| KICK/FIXED HOUSING | E | 38.6 | 0.98 |
| BIT TO BEND (ADJUSTABLE) | F1 | 55.8 | 1.42 |
| ADAPTOR HOUSING (ADJUSTABLE) | G1 | 60.8 | 1.54 |
| BIT TO BEND (FIXED) | F2 | 45.6 | 1.16 |
| ADAPTOR HOUSING (FIXED) | G2 | 52.3 | 1.33 |
| STATOR START | H | 77.0 | 1.96 |
| STATOR END | I | 306.3 | 7.78 |
| OVERALL LENGTH | J | 337.4 | 8.57 |
| BIT BOX Ø | K | 4.63 | 117.6 |
| END CAP/BEARING HOUSING Ø | L | 5.15 | 130.8 |
| THREAD PROTECTOR Ø | M | 5.75 | 146.1 |
| PISTON HOUSING Ø | N | 5.15 | 130.8 |
| KICK/FIXED HOUSING Ø | O | 5.06 | 128.5 |
| PAD (ADJUSTABLE) Ø | P1 | 5.50 | 139.7 |
| PAD (FIXED) Ø | P2 | 5.38 | 136.7 |
| ADJUSTABLE MANDREL PIN Ø | Q | 2.81 | 71.4 |
| ADAPTOR HOUSING Ø | R | 5.06 | 128.5 |
| ADAPTOR PIN Ø | S | 3.35 | 85.1 |
| STATOR TUBE OUTER Ø | T | 5.00 | 127.0 |
| STATOR TUBE INNER Ø | U | 3.75 | 95.3 |
| ROTOR CATCH SUB BLADE Ø | V | 5.25 | 133.4 |
| ROTOR CATCH SUB Ø | W | 5.00 | 127.0 |



| INTERNALS | | USC | SI |
|----------------------------|---|-------|-------|
| BIT BOX | A | 8.0 | 0.20 |
| THRUST SHOULDER | B | 16.2 | 0.41 |
| WASHPIPE START | C | 20.4 | 0.52 |
| HEX END | D | 25.7 | 0.65 |
| BEARING ASSEMBLY ADAPTOR | E | 37.5 | 0.95 |
| BAA CAP | F | 47.9 | 1.22 |
| ROTOR ADAPTOR CAP | G | 70.9 | 1.80 |
| ROTOR START | H | 76.9 | 1.95 |
| ROTOR END | I | 296.9 | 7.54 |
| CATCH STEM | J | 308.8 | 7.84 |
| BIT BOX Ø | K | 4.63 | 117.6 |
| MANDREL Ø | L | 3.63 | 92.2 |
| THRUST Ø | M | 3.13 | 79.5 |
| WASHPIPE LARGE Ø | N | 4.00 | 101.6 |
| WASHPIPE SMALL Ø | O | 3.00 | 76.2 |
| BEARING ASSEMBLY ADAPTOR Ø | P | 3.58 | 90.9 |
| DRIVESHAFT Ø | Q | 1.93 | 49.0 |
| ROTOR ADAPTOR Ø | R | 3.60 | 91.4 |
| ROTOR MAJOR DIA. Ø | S | 3.09 | 78.5 |
| ROTOR CATCH STEM Ø | T | 2.13 | 54.0 |

This information is for reference only. Assemblies are displayed in an "Adjustable Configuration"

Rotor Catch and Rotor Catch Float Sub Lengths may vary based on configuration, and use of Dump Subs or combination Rotor Catch and Float Housings.

If any additional information is required, please contact your local DYNOMAX office.