




Bit Size Range	8-1/2 - 9-7/8 in	216 - 251 mm
Bit Box Connection	4-1/2 REGULAR	
Dynamic Bearing Load On/Off Bottom	151925 lbf	67600 daN
Static Bearing Load On/Off Bottom	509765 lbf	226800 daN
Max. Overpull (For Re-run)	509765 lbf	226800 daN
Absolute Overpull	742200 lbf	330100 daN
Adjustable Makeup Torque	32000 ft-lbs	43400 Nm
Stab/Thread Protector Makeup Torque	15000 ft-lbs	20300 Nm
A = Bit to Stabilizer (Centre)	17 in	0.43 m
B = Bit to Bend	Adjustable 68 in Fixed 56.3 in	1.73 m 1.43 m
C = Overall (With Dump Sub)	406.5 in	10.33 m
Weight	3074 lb	1394 kg

Lobe Configuration	6-7 Lobe 8.4 Stage HR	
Displacement (No Load)	0.3 rev/gal	0.08 rev/l
Max. Differential (Full Load)	1980 psi	13652 kPa
Max. Torque	16550 ft-lbs	22439 Nm
Max. Power	599 HP	446 kW

Flow Rate		Speed
GPM	LPM	RPM
350	51325	75 - 110
550	2082	133 - 170
750	2839	190 - 230



Possible damage may occur when motor is run higher than 70% of Maximum Differential Pressure.

ADJUSTABLE BUILD RATE

Hole Size	SLICK				STABILIZED			
	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
0.39	0.8	0.2	-	-	2.0	2.1	2.6	2.6
0.78	3.2	2.7	0.1	0.1	4.0	4.1	4.7	4.7
1.15	5.5	4.9	2.4	2.4	6.0	6.1	6.7	6.7
1.50	7.7	7.1	4.6	4.6	7.8	8.0	8.5	8.5
1.83	9.7	9.1	6.6	6.6	9.7	9.7	10.3	10.3
2.12	11.5	10.9	8.4	8.4	11.5	11.3	11.8	11.8
2.38	13.1	12.5	10.0	10.0	13.1	12.6	13.2	13.2
2.60	14.5	13.9	11.4	11.4	14.5	13.9	14.3	14.3
2.77	15.5	14.9	12.4	12.4	15.5	14.9	15.3	15.3
2.90	16.3	15.8	13.2	13.2	16.3	15.8	15.9	15.9
2.97	16.7	16.2	13.7	13.7	16.7	16.2	16.3	16.3
3.00	16.9	16.4	13.9	13.9	16.9	16.4	16.5	16.5

Note: Stabilizers are 1/8" undergage

FBH BUILD RATE

Hole Size	SLICK				STABILIZED			
	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
1.25	5.8	5.1	2.2	2.2	6.8	6.9	7.4	7.4
1.50	7.3	6.7	3.7	3.7	8.1	8.3	8.8	8.8
1.75	8.9	8.2	5.2	5.2	9.5	9.6	10.2	10.2
2.00	10.4	9.7	6.8	6.8	10.9	11.0	11.6	11.6
2.25	11.9	11.3	8.3	8.3	12.3	12.4	12.9	12.9
2.50	13.5	12.8	9.9	9.9	13.6	13.8	14.3	14.3

This information is for reference only. Build rates are theoretical calculations using three-point geometry and new motor builds. Actual rate predictions will depend on formation characteristics, bit profiles, and WOB.

For custom motor configurations and build rates, please contact your DYNOMAX office.

FISHING DIMENSIONS

USC - IMPERIAL (Lengths, Diameters = in)
SI - METRIC (Lengths = m, Diameters = mm)



EXTERNALS		USC	SI
END CAP	A	11.2	0.28
BEARING HOUSING	B	--	--
PISTON HOUSING	C	17.8	0.45
STABILIZER SHOULDER	D	34.3	0.87
KICK/FIXED HOUSING	E	44.9	1.14
BIT TO BEND (ADJUSTABLE)	F1	68.0	1.73
ADAPTOR HOUSING (ADJUSTABLE)	G1	73.9	1.88
BIT TO BEND (FIXED)	F2	56.3	1.43
ADAPTOR HOUSING (FIXED)	G2	66.5	1.69
STATOR START	H	98.5	2.50
STATOR END	I	373.5	9.49
OVERALL LENGTH	J	406.5	10.33
BIT BOX Ø	K	6.38	162.1
END CAP/BEARING HOUSING Ø	L	7.00	177.8
THREAD PROTECTOR Ø	M	7.75	196.9
PISTON HOUSING Ø	N	7.15	181.6
KICK/FIXED HOUSING Ø	O	7.15	181.6
PAD (ADJUSTABLE) Ø	P1	7.38	187.5
PAD (FIXED) Ø	P2	7.38	187.5
ADJUSTABLE MANDREL PIN Ø	Q	4.22	107.2
ADAPTOR HOUSING Ø	R	7.15	181.6
ADAPTOR PIN Ø	S	5.04	127.9
STATOR TUBE OUTER Ø	T	7.00	177.8
STATOR TUBE INNER Ø	U	5.75	146.1
ROTOR CATCH SUB BLADE Ø	V	7.25	184.2
ROTOR CATCH SUB Ø	W	7.00	177.8



INTERNALS		USC	SI
BIT BOX	A	10.0	0.25
THRUST SHOULDER	B	22.9	0.58
WASHPIPE START	C	28.0	0.71
HEX END	D	34.2	0.87
BEARING ASSEMBLY ADAPTOR	E	43.1	1.09
BAA CAP	F	58.8	1.49
ROTOR ADAPTOR CAP	G	90.6	2.30
ROTOR START	H	99.2	2.52
ROTOR END	I	366.2	9.30
CATCH STEM	J	383.7	9.75
BIT BOX Ø	K	6.38	162.1
MANDREL Ø	L	5.25	133.4
THRUST Ø	M	4.49	114.0
WASHPIPE LARGE Ø	N	5.50	139.7
WASHPIPE SMALL Ø	O	4.25	108.0
BEARING ASSEMBLY ADAPTOR Ø	P	5.00	127.0
DRIVESHAFT Ø	Q	3.00	76.2
ROTOR ADAPTOR Ø	R	5.00	127.0
ROTOR MAJOR DIA. Ø	S	4.75	120.6
ROTOR CATCH STEM Ø	T	3.19	81.0

This information is for reference only. Assemblies are displayed in an "Adjustable Configuration"

Rotor Catch and Rotor Catch Float Sub Lengths may vary based on configuration, and use of Dump Subs or combination Rotor Catch and Float Housings.

If any additional information is required, please contact your local DYNOMAX office.